



REFERENCE SHEET

SELF-ADHESIVE

338.2K

KLING FILM – WHITE

Repositionable adhesive-backed film for imaging by the ink jet process, providing a colored image on a white background. Film is designed as a “universal” product for use in all ink jet printers.

Availability: 8.5 x 11 and A4 sheets.

Features: Create colorful panels to place on glass* and other smooth inside surfaces. Film is fast drying, fade resistant and smear resistant as well as having non-tear properties for durability.

Technical Properties

Smoothness, Sheffield:	10±6 per TAPPI T538 Test Method.
Opacity, %:	89 minimum per TAPPI T425 Test Method.
Brightness:	84 minimum per TAPPI T452 Test Method.
Whiteness:	98 minimum per CIE Lab Test Method.
60° Gloss:	94 minimum per ASTM D2457 Test Method.
Optimal Service Environment:	Between 59° and 86°F. and 30% to 70% RH.
Print Resolution:	Dependent upon printer used.
Ideal Storage Conditions:	Between 59° and 77°F. and 30% to 70% RH.
Shelf Life:	Minimum of 2 years from Arkwright ship date when stored under ideal storage conditions (see above).

Application Guidelines

PRINTING INSTRUCTIONS

1. Handle film by the edges to avoid fingerprints.
2. The reverse side of the “image other side” indication is the imaging side of the film.
3. For multiple images, fan the required number of sheets before stacking in paper tray. Note some printers may require single-sheet feeding.
4. Let film dry a few minutes before re-stacking.
5. When ready to apply image to inside clear/standard glass surfaces, peel off the backing sheet at the side score line.

OTHER INFORMATION

- Make sure to select the proper media setting (photo paper or ink jet transparency) from the print menu.
- Check your printer manual for additional printing instructions. Not recommended for printers such as HP DeskJet 1200C or 1600C models because they apply heat.
- If this product is applied to any substrate other than clear/standard (non-tinted, non-treated) glass, test a small surface area to ensure compatibility.
- Before printing final image, produce on economy grade ink jet paper to test for layout and design.
- Keep product in closed package between uses; store in a cool, dry place.

*If this product is applied to any substrate other than clear/standard (non-tinted, non treated) glass, test a small surface area to ensure compatibility. Arkwright believes that the information set forth herein is reliable. The information is intended for use by persons having technical skill at their own discretion. Since conditions of use are outside of Arkwright's control, we make no warranties, expressed or implied, and assume no liability in connection with any use of this information.

ARKWRIGHT

Arkwright, Inc., 538 Main Street, Fiskeville, RI 02823, p. 401.821.1000, f. 401.826.3926.
www.arkwright.com
Arkwright is a registered trademark of Arkwright, Inc. © 2005 Arkwright, Inc., rev. 01 (08/05)