



OFFICE

OFFICE

REFERENCE SHEET

FILMS – COLOR LASER COPIERS/PRINTERS - PLAIN PAPER COPIERS –
MONOCHROME LASER PRINTERS

073.41

DURACOPY (WHITE FILM), 3-HOLE PUNCHED

A durable, tear and stain resistant 3-hole punched film for imaging by xerographic process, providing a dense black image on a bright white background. Film is designed for use in virtually all copiers.

Availability:	8.5 x 11 and 11 x 17 sheets
Features:	White Opaque Film that provides excellent color saturation, print resolution, print resolution and high quality output. Can be printed on either side.

Technical Properties

Total Thickness:	4.6 mil ± 0.3 per ASTM D654 Test Method.
Smoothness, Sheffield:	100 ± 40 per TAPPI T538 Test Method.
Opacity, %:	88 minimum per TAPPI T425 Test Method.
Gloss, 60°:	10 maximum per ASTM D2457 Test Method.
Brightness:	90 minimum per ASTM D985 Test Method.
Optimal Service Environment:	Between 59° and 86°F and 30% to 70% RH.
Copy Resolution:	Dependent upon copier used.
Ideal Storage Conditions:	Between 59° and 77°F and 30% to 70% RH.
Shelf Life:	Minimum of 2 years from Arkwright ship date when stored under ideal storage conditions (see above).

Application Guidelines

INSTRUCTIONS FOR USE

1. Keep film stored in its original box until ready to use. Store under normal office temperature and humidity conditions.
2. Handling the film along the edges will avoid fingerprints on image area.
3. Fan the required number of sheets of film (as you would paper) to facilitate feeding.
4. Most color copiers/printers require that film be fed through the bypass of the machine according to its instructions. Film can be imaged on either side.
5. It is recommended to wait a few minutes after imaging to allow film to dry before handling.

HELPFUL HINTS

1. Before printing final image test on economy grade paper for layout, placement and design.

Arkwright believes that the information set forth herein is reliable. The information is intended for use by persons having technical skill at their own discretion. Since conditions of use are outside of Arkwright's control, we make no warranties, expressed or implied, and assume no liability in connection with any use of this information.

ARKWRIGHT

Arkwright, Inc., 538 Main Street, Fiskeville, RI 02823, p. 401.821.1000, f. 401.826.3926.
www.arkwright.com
Arkwright is a registered trademark of Arkwright, Inc. © 2005 Arkwright, Inc., rev. 01 (08/05)