



REFERENCE SHEET

SELF-ADHESIVE

655-2K

CLEAR LASER CLING DECAL

Clear Laser Cling Film that provides excellent color saturation, print resolution and high quality output on a clear face side and a cling adhesive on the back. Film is optically clear, heat stable, smudge, fade and water resistant. The film is designed as a “universal” product for use in all digital copier/printers.

Availability: 8.5 x 11, 11 x 17 , A4 and A3 sheets

Features: Designed for use with all digital copier/printers. Images have improved sharpness and color vibrancy because of high black and color optical densities. Heat stable, fade resistant and smear resistant.

Technical Properties

Smoothness, Sheffield:	20±15per TAPPI T538 Test Method.
Haze, %(w/o liner):	4±3 per ASTM D1003 Test Method.
Log Surface Resistivity:	10.5±1.5 Ω^2 per AI Test Method..
Heat Distortion:	1.0% maximum per AI Test Method.
Toner Adhesion:	Pass crease test per AI Test Method.
180° Peel Adhesion, g/in.:	12±10 per ASTM D3330 Test Method.
Optimal Service Environment:	Between 15° and 30°C. and 30% to 70% RH.
Print Resolution:	Dependent upon copier/printer used.
Ideal Storage Conditions:	Between 15° and 25°C.and 30% to 70% RH.
Shelf Life:	Minimum of 2 years from Arkwright ship date when stored under ideal storage conditions (see above).

Application Guidelines

INSTRUCTIONS FOR USE

1. Keep film stored in its original box until ready to use. Store under normal office temperature and humidity conditions.
2. Handling the film along the edges will avoid fingerprints on image area.
3. Fan the required number of sheets of film (as you would paper) to facilitate feeding.
4. The glossy (shiny) side is the imaging side .
5. Most color copiers/printers require that film be fed through the bypass of the machine according to its instructions.
6. Do not remove backing sheet before imaging.
7. After imaging, separate the backing sheet from the imaged sheet by gently peeling at the score line on the reverse side. Remove backing sheet in one continuous, rapid motion.
8. Apply to clean, dry window or other smooth surface.
9. To avoid air pockets, do not apply pressure to the decal once it has been applied to the surface.

HELPFUL HINTS

1. Before printing final image test on economy grade paper for layout, placement and design.
2. Do not image beyond the score line.
3. Product is repositionable. Simply remove and re-apply to new area.

Arkwright believes that the information set forth herein is reliable. The information is intended for use by persons having technical skill at their own discretion. Since conditions of use are outside of Arkwright's control, we make no warranties, expressed or implied, and assume no liability in connection with any use of this information.

ARKWRIGHT

Arkwright, Inc., 538 Main Street, Fiskeville, RI 02823, p. 401.821.1000, f. 401.826.3926.
www.arkwright.com
Arkwright is a registered trademark of Arkwright, Inc. © 2005 Arkwright, Inc., rev. 01 (08/05)