



OFFICE OFFICE

REFERENCE SHEET

PLAIN PAPER COPIER FILMS

694.00

TRANSPARENCY - NO STRIPE

Film for imaging by xerographic process, providing a dense black image on a transparent background. Film is designed for use in virtually all copiers.

Availability: 8.5 x 11, 11 X 17, A4 and A3 sheets

Technical Properties

Smoothness, Hagerty:	10±6 per TAPPI T538 Test Method.
Haze, %:	6 maximum per ASTM D1003 Test Method.
Optimal Service Environment:	Between 59° and 86°F and 30% to 70% RH.
Copy Resolution:	Dependent upon copier used.
Ideal Storage Conditions:	Between 59° and 77°F and 30% to 70% RH.
Shelf Life:	Minimum of 2 years from Arkwright ship date when stored under ideal storage conditions (see above).

Application Guidelines

INSTRUCTIONS FOR USE

1. Keep film stored in its original box until ready to use. Store under normal office temperature and humidity conditions.
2. Handling the film along the edges will avoid fingerprints on image area.
3. Fan the required number of sheets of film (as you would paper) to facilitate feeding.
4. Film can be imaged either side.
5. Most plain paper copiers require that film be fed through the bypass of the machine according to its instructions. Film can be imaged on either side.
6. Many users interleave imaged film with plain paper for ease of handling. This will also aid in absorbing fuser oil deposited on the film by some copiers.

Arkwright believes that the information set forth herein is reliable. The information is intended for use by persons having technical skill at their own discretion. Since conditions of use are outside of Arkwright's control, we make no warranties, expressed or implied, and assume no liability in connection with any use of this information.

ARKWRIGHT

Arkwright, Inc., 538 Main Street, Fiskeville, RI 02823, p. 401.821.1000, f. 401.826.3926.
www.arkwright.com
Arkwright is a registered trademark of Arkwright, Inc. © 2005 Arkwright, Inc., rev. 01 (08/05)