



REFERENCE SHEET

MULTIFUNCTION (INK JET/LASER/PPC) FILMS

380.45

TRANSPARENCY – REMOVABLE TOP STRIPE

A multifunctional transparency film that can be used in ink jet printers, monochrome laser printers, plain paper copiers and selected color laser printers/copiers. The film is designed as a “universal” product for use in all ink jet printers and monochrome printers/copiers.

Availability:	8.5 x 11 and A4 sheets
Features:	Produces brilliant and sharp monochrome and color images. Fast drying, fade resistant and smear resistant when using ink jet printers. Most versatile multifunctional transparency marketed.

Technical Properties

Smoothness, Sheffield:	per TAPPI T538 Test Method. Ink Jet Image Side – 350 ±50 Back Image Side – 30 ± 20
Haze, %:	7.0 maximum per ASTM D1003 Test Method.
Product Weight,gsm:	175 ± 10 per TAPPI T410 Test Method.
Total Thickness, mils:	5.3 ± 0.3 per TAPPI T411 Test Method.
Curl, mm:	0 ± 12.5 per AI TM208.24 Test Method.
Optimal Service Environment:	Between 15° and 30°C. and 30% to 70% RH.
Print Resolution:	Dependent upon copier/printer used.
Ideal Storage Conditions:	Between 15° and 25°C. and 30% to 70% RH.
Shelf Life:	Minimum of 2 years from Arkwright ship date when stored under ideal storage conditions (see above).

Application Guidelines

INSTRUCTIONS FOR USE

1. Keep film stored in its original package until ready to use. Store and image under normal office temperature and humidity conditions.
2. Handling the film along the edges will avoid fingerprints on image area.
3. Fan the required number of sheets of film (as you would paper) to facilitate feeding. Place film in paper tray, orienting film as indicated in application section below.
4. Many users interleave imaged film with plain paper for ease of handling.
5. Most color copiers require that transparency film be fed through the bypass of the machine according to its instructions. Make sure the stripe is at the leading edge of the paper tray.

FOR PRINTING

1. The side opposite the removable stripe is the imaging side for ink jet printing.
2. The side with the removable stripe is the imaging side for laser/copier printing.
3. Make sure the edge with the removable stripe is the leading edge.

Arkwright believes that the information set forth herein is reliable. The information is intended for use by persons having technical skill at their own discretion. Since conditions of use are outside of Arkwright's control, we make no warranties, expressed or implied, and assume no liability in connection with any use of this information.

ARKWRIGHT

Arkwright, Inc., 538 Main Street, Fiskeville, RI 02823, p. 401.821.1000, f. 401.826.3926.
www.arkwright.com
Arkwright is a registered trademark of Arkwright, Inc. © 2005 Arkwright, Inc., rev. 01 (08/05)