



DISPLAY GRAPHICS

DISPLAY GRAPHICS

DATA SHEET

BACKLIT FILMS

341-70

FRONT PRINT BACKLIT FILM

This 7 mil front Backlit film provides high color saturation, brilliant colors and a extremely durable coating. The advantages of Front Print Backlit Film include high ink load retention, high resolution and fast drying.

Main Applications:	Indoor Signage High durable displays Economic cost structure
Features:	Brilliant colors with Dye based inks Durable 7 mil polyester Long Lasting images both indoors and outdoors Easy to handle Excellent color space Very quick dry times
Availability:	100 ft. rolls in 24", 36", 42", 50" and 60" 75 ft. rolls in 36" and 54"
Basis Weight:	280 gsm
Opacity, %:	60% per TAPPI T-425
Caliper:	7.5 mil nominal
Brightness:	75 per TAPPI T-452
Whiteness:	65 per CIE Ganz 82
Smoothness, Sheffield:	12 per TAPPI T-538
Optimal print conditions:	Between 59° and 86°F ; 30% to 70% RH.
Shelf Life:	2 years
Storage Conditions:	Temperature: 50° and 86°F RH%: 30% to 70% Repack open rolls Allow material to adapt to room conditions

Arkwright believes that the information set forth herein is reliable. The information is intended for use by persons having technical skill at their own discretion. Since conditions of use are outside of Arkwright's control, we make no warranties, expressed or implied, and assume no liability in connection with any use of this information.

ARKWRIGHT

Arkwright, Inc., 538 Main Street, Fiskeville, RI 02823, p. 401.821.1000, f. 401.826.3926.
www.arkwright.com
Arkwright is a registered trademark of Arkwright, Inc. © 2002 Arkwright, Inc., rev. 01 (07/02)