



DISPLAY GRAPHICS

DISPLAY GRAPHICS

DATA SHEET

BACKLIT FILMS

551-50

5 MIL REVERSE PRINT BACKLIT FILM

This 5 mil reverse print Backlit film provides high color saturation, brilliant colors and a extremely durable coating. The advantages of Reverse Backlit Film include protection of the graphics in high traffic areas, high resolution and fast drying.

Main Applications:	Indoor Signage High traffic areas where image protection is required
Features:	Brilliant colors with Dye based inks. Durable 5 mil polyester Long Lasting images both indoors and outdoors Easy to handle Excellent color space Very quick dry times
Availability:	100 ft. rolls in 24", 36", 42", 50", 54" and 60"
Basis Weight:	190 gsm
Opacity, %:	63% per TAPPI T-425
Caliper:	5.3 mil nominal
Brightness:	83 per TAPPI T-452
Whiteness:	56 per CIE Ganz 82
Smoothness, Sheffield:	9 per TAPPI T-538
Optimal print conditions:	Between 59° and 86°F and 30% to 70% RH.
Shelf Life:	2 years
Storage Conditions:	Temperature: 50° and 86°F RH % : 30% to 70%

Arkwright believes that the information set forth herein is reliable. The information is intended for use by persons having technical skill at their own discretion. Since conditions of use are outside of Arkwright's control, we make no warranties, expressed or implied, and assume no liability in connection with any use of this information.

ARKWRIGHT

Arkwright, Inc., 538 Main Street, Fiskeville, RI 02823, p. 401.821.1000, f. 401.826.3926.
www.arkwright.com
Arkwright is a registered trademark of Arkwright, Inc. © 2002 Arkwright, Inc., rev. 01 (07/02)