



DISPLAY GRAPHICS

DISPLAY GRAPHICS

DATA SHEET

SOLVENT

760.90 - 761.12

**Solvent Semi Rigid Display Film**

760.90 (9 mil) and 761.12 (12 mil); a semi rigid PVC with a bright white coating designed specifically for eco/mild, standard and hot solvent inkjet printers. This superior coating provides a water fast, quick dry, and exceptional print quality to an economical base.

760.90 and 761.12 can be used for roll-up displays and other P.O.P. applications.

<u>760.90</u>	
<b>Caliper:</b>	9 mil
<b>Opacity:</b>	98%
<b>Whiteness:</b>	86 (We)
<b>Gloss:</b>	14 @ 60°

<u>761.12</u>	
<b>Caliper:</b>	11.5 mil
<b>Opacity:</b>	98%
<b>Whiteness:</b>	88 (We)
<b>Gloss:</b>	14 @ 60°

<i>Feature</i>	<i>Advantage</i>	<i>Benefit</i>
Satin coating	Reduced glare image	Perfect for low glare vivid images
Durable solvent ink coating	Long lasting images	No secondary processing required
High quality PVC Base	Reduced Curl	Save time and money on processing

**Optimal Storage Conditions:** Temperature 59° - 86° F - Humidity 30% - 70% RH

**Shelf Life:** One year stored at above conditions, unopened in original packaging

Arkwright believes that the information set forth herein is reliable. The information is intended for use by persons having technical skill at their own discretion. Since conditions of use are outside of Arkwright's control, we make no warranties, expressed or implied, and assume no liability in connection with any use of this information.

**ARKWRIGHT**  
ADVANCED COATING, INC

Arkwright Advanced Coating, Inc. 538 Main Street Fiskeville, RI 02823 p: 401.821.1000  
9/2/2008