



DISPLAY GRAPHICS

# DISPLAY GRAPHICS

DATA SHEET

**SOLVENT**

## 780.50

**Solvent 6.5 mil Matte Backlit**

780.50 is a 6.5 mil polyester coated backlit film. The coating is specifically design for eco/mild, standard, and hot solvent inkjet printers. This matte waterproof coating is designed to provide maximum image density when properly profiled.

<b>Basis Weight:</b>	180 gsm
<b>Caliper:</b>	6.2 mil
<b>Opacity:</b>	78%
<b>Gloss:</b>	matte

<i>Feature</i>	<i>Advantage</i>	<i>Benefit</i>
Specifically design solvent inkjet	Highest image density	Better transmitted image performance
Matte finish	Reduce glare, improve density	Best in class performance
Water-resistant	No need for secondary process	Save time and money

**Optimal Storage Conditions:** Temperature 59° - 86° F - Humidity 30% - 70% RH

**Shelf Life:** One year stored at above conditions, unopened in original packaging

Arkwright believes that the information set forth herein is reliable. The information is intended for use by persons having technical skill at their own discretion. Since conditions of use are outside of Arkwright's control, we make no warranties, expressed or implied, and assume no liability in connection with any use of this information.

**ARKWRIGHT**  
ADVANCED COATING, INC

Arkwright Advanced Coating, Inc. 538 Main Street Fiskeville, RI 02823 p: 401.821.1000  
9/2/2008