



DISPLAY GRAPHICS

DISPLAY GRAPHICS

DATA SHEET

PRESENTATION PAPERS

813.35

**35LB. PRESENTATION PAPER**

***This 35 lb. product provides superior color saturation; print resolution and high quality output with no glare and fast dry times. An inexpensive graphic display media designed to maximize your profit. 813.35 is your solution for economical trade show graphics and posters.***

Main Applications:	Indoor Signage Point of Purchase Displays Mounted Posters (exhibits and trade show graphics)
Features:	True dye and pigment ink compatibility Very quick, dry time Excellent Lamination Easy to handle and laminate Excellent color space Great alternative to Photo Paper
Construction:	130-gsm with an ink jet receptive coating Backside is coated to reduce curl and enhance performance
Availability:	100 foot rolls in 24", 36", 42", 50", 54" and 60"
Caliper:	7.0 mil nominal
Opacity, %:	95 minimum per TAPPI T425 Test Method.
Whiteness:	108 minimum per CIE Ganz 82 Test Method.
Optimal Service Environment:	Between 59° and 86°F and 30% to 70% RH.
Print Resolution:	Dependent upon printer used.
Ideal Storage Conditions:	Between 59° and 77°F and 30% to 70% RH. (Always repack unfinished rolls in poly bag!)
Shelf Life:	Minimum of 1 year from Arkwright ship date when stored under ideal storage conditions (see above).

Arkwright believes that the information set forth herein is reliable. The information is intended for use by persons having technical skill at their own discretion. Since conditions of use are outside of Arkwright's control, we make no warranties, expressed or implied, and assume no liability in connection with any use of this information.

**ARKWRIGHT**

Arkwright, Inc., 538 Main Street, Fiskeville, RI 02823, p. 401.821.1000, f. 401.826.3926,  
www.arkwright.com  
Arkwright is a registered trademark of Arkwright, Inc. © 2004 Arkwright, Inc., rev. 02 (07/04)