



DISPLAY GRAPHICS

DISPLAY GRAPHICS

DATA SHEET

223.40 - 221.50 - 222.70 - 224.50

UV Curable Compatible

Semi Rigid Display Films

This new line of display films are high quality dimensionally stable polyester films that are designed with a treatment to enhance the adhesion of UV curable inks from new UV Curable inkjet printers. All have an antistatic back coat to reduce static.

223.40 - 4 mil UV White Film

Caliper:	4 mil
Opacity:	92%
Whiteness:	100 (We)
Brightness:	92
Gloss:	61 @ 60°
Smoothness:	5.2 Sheffield Units

221.50 - 5 mil UV Grey Back Film

Caliper:	5 mil
Opacity:	100%
Whiteness:	100 (We)
Brightness:	81
Gloss:	60 @ 60°
Smoothness:	7.3 Sheffield Units

222.70 - 7 mil UV Clear Film

Caliper:	7 mil
Haze:	2.4
Gloss:	180 @ 60°
Smoothness:	12 Sheffield Units

224.50 - 5 mil UV Backlit

Caliper:	5 mil
Opacity:	60%
Gloss:	110 @ 60°
Smoothness:	21 Sheffield Units

Optimal Storage Conditions: Temperature 59° - 86° F - Humidity 30% - 70% RH

Shelf Life: One year stored at above conditions, unopened in original packaging

Arkwright believes that the information set forth herein is reliable. The information is intended for use by persons having technical skill at their own discretion. Since conditions of use are outside of Arkwright's control, we make no warranties, expressed or implied, and assume no liability in connection with any use of this information.

ARKWRIGHT
ADVANCED COATING, INC

Arkwright Advanced Coating, Inc. 538 Main Street Fiskeville, RI 02823 p: 401.821.1000
9/2/2008