

# 3482k

## Universal Clear Film with Cling Adhesive

### PRODUCT DESCRIPTION

3482k - **Universal Clear Film with Cling Adhesive** is a 2 mil tear resistant polyester film with a clear inkjet topcoat and a clear removable cling adhesive. The inkjet topcoat is universally compatible for dye and pigment ink and will provide brilliant graphics that can be mounted to interior doors, windows or glass partitions.

### SPECIFICATIONS

Caliper	2 mil
Haze	4
Smoothness	25

\*All values listed are target values

FEATURE	ADVANTAGE
Polyester Film	Dimensionally Stable / Tear Resistant
Cling Adhesive	Removable - Easy on/off
Very Clear	Great for Windows and Glass Doors
Universal Compatibility	One Sku For All Printers

SIZE	PART NUMBER	CORE
42" x 100'	3482K00029H9	2"

### PRINTER

Hewlett Packard DJ Z 2100, 3100, 6100  
Hewlett Packard DJ 5000 / 5500 /  
Epson Pro 4000, 7600, 9600, 10600  
Epson Stylus Pro 4800, 4880, 7800, 7880, 9800, 9880, 11880  
Canon iPF 5000, 5100, 6100, 8000, 8100, 9000, 9100

### INK

Vivera Pigment  
Dye / UV  
Ultra Chrome  
K3  
Lucia Pigment

### FINISHING RECOMENDATIONS

Protect prints imaged with dye inks under glass or laminate to increase gas-fastness.  
Use low melt or pressure sensitive laminates to extend the life of the print and increase its durability.  
For best results use thinner and flexible laminates.  
Allow 24 hours for ink to cure before protecting image.

### STORAGE CONDITIONS

Temperature 59o-86oF. (15°-30°C).  
Repack opened rolls when not in use.  
One year shelf life at conditions noted above.  
Allow material to stabilize to room conditions for 24 hours before use.