

# 34848

## Universal Clear Film with Interleaf - GLOSS

### 4 mil

**PRODUCT DESCRIPTION**

34848 is an extremely clear 4 mil polyester film. The universal topcoat is designed to provide excellent print performance and still maintain the extreme clarity of the film. 34848 features an acid free interleaf paper for HP and other printers that search for the media edge before printing. The interleaf paper also helps reduce scratches from the printer feed mechanisms and provides a protective wrap for final prints.

**SPECIFICATIONS**

Caliper	4 mil
Haze	<5%
Gloss (60°)	90
Smoothness	<45

\*All values listed are target values

FEATURE	ADVANTAGE
Extremely Clear	Great overlays, color keys and glass applications
Low Haze	Very clear
Very Smooth	Improved print performance
Universal Compatibility	Reduce SKUs
Acid Free Interleaf Liner	Protects film through the printer
Available without Removeable Side Strip (348.40)	Select the right version for your printer workflow

SIZE	PART NUMBER	CORE
24" x 100'	348480001509	2"
36" x 100'	348480002409	2"
42" x 100'	348480002909	2"
50" x 100'	348480003709	2"

**PRINTER**

Hewlett Packard DJ Z 2100, 3100, 6100  
 Hewlett Packard DJ 5000 / 5500 /  
 Epson Pro 4000, 7600, 9600, 10600  
 Epson Stylus Pro 4800, 4880, 7800, 7880, 9800, 9880, 11880  
 Canon iPF 5000, 5100, 6100, 8000, 8100, 9000, 9100

**INK**

Vivera Pigment  
 Dye / UV  
 Ultra Chrome  
 K3  
 Lucia Pigment

**FINISHING RECOMENDATIONS**

Protect prints imaged with dye inks under glass or laminate to increase gas-fastness.  
 Use low melt or pressure sensitive laminates to extend the life of the print and increase its durability.  
 For best results use thinner and flexible laminates.  
 Allow 24 hours for ink to cure before protecting image.

**STORAGE CONDITIONS**

Temperature 59o-86oF. (15°-30°C).  
 Repack opened rolls when not in use.  
 One year shelf life at conditions noted above.  
 Allow material to stabilize to room conditions for 24 hours before use.