

# 37915 Ultra-Durable™ Scrim Vinyl with Blockout - MATTE 15 mil

**PRODUCT DESCRIPTION**

379.15 Universal 15mil Scrim Vinyl is a true universal performer with both dye and pigmented aqueous ink sets. This bright white robust 15mil scrim with block-out is great for indoor as well as outdoor applications. Universal Scrim can be easily grommeted, sewn and laminated if desired. Once printed with pigment inks and allowed to dry, the media and inks are water fast and suitable for 6 months outdoors unlaminated and up to a year when laminated.

**SPECIFICATIONS**

Caliper 15 mil  
Gloss (60°) matte  
Opacity >99%

\*All values listed are target values

FEATURE	ADVANTAGE
Blockout Layer	100% Opacity, Prevents show-through
Outdoor Durable up to 12 months	Short term outdoor use
Smooth Finish	Improves print performance
Good Tear-Resistance	Resists tearing from wind
Suitable for Grommeting and Welding	Easy to hang and display
Waterfast Coating	Outdoor durable

SIZE	PART NUMBER	CORE
24" x 45'	3791500015BL	2"
36" x 45'	3791500024BL	2"
42" x 45'	3791500029BL	2"
50" x 45'	3791500037BL	2"
60" x 45'	3791500045BL	2"

**PRINTER**

Hewlett Packard DJ Z 2100, 3100, 6100  
Hewlett Packard DJ 5000 / 5500 /  
Epson Pro 4000, 7600, 9600, 10600  
Epson Stylus Pro 4800, 4880, 7800, 7880, 9800, 9880, 11880  
Canon iPF 5000, 5100, 6100, 8000, 8100, 9000, 9100

**INK**

Vivera Pigment  
Dye / UV  
Ultra Chrome  
K3  
Lucia Pigment

**FINISHING RECOMENDATIONS**

Protect prints imaged with dye inks under glass or laminate to increase gas-fastness.  
Use low melt or pressure sensitive laminates to extend the life of the print and increase its durability.  
For best results use thinner and flexible laminates.  
Allow 24 hours for ink to cure before protecting image.

**STORAGE CONDITIONS**

Temperature 59o-86oF. (15°-30°C).  
Repack opened rolls when not in use.  
One year shelf life at conditions noted above.  
Allow material to stabilize to room conditions for 24 hours before use.



Arkwright Advanced Coating, Inc.  
538 Main Street, Fiskeville, RI 02823,  
p. 401.821.1000, f. 401.826.3926  
www.arkwright.com

Arkwright is a registered trademark of Arkwright Advanced Coating, Inc © 2009