

# 38240

## Universal White Film - GLOSS

### 4 mil

**PRODUCT DESCRIPTION**

38240 is the classic rollup display film. 4 mil, high gloss finish, durable polyester base and unsurpassed imaging performance. 38240 is designed for use with thermal dye and pigment ink printers. Laminate with pressure sensitive or low melt overlaminate for a ultra durable rollup display.

**SPECIFICATIONS**

Caliper	4 mi
Gloss (60°)	90
Opacity	93%
Whiteness	>110

\*All values listed are target values

FEATURE	ADVANTAGE
Hybrid Ozone Resistant Coating	Colors wont fade without lamination when printed with dye inks
Unsurpassed Image Quality	Very Durable - Not a laminated base
Outstanding Lamination Bond	Indestructable graphics
High Gloss Photo Finish	Outstandiing Print Quality
Lay Flat	Reduces curl and cupping
Universal Compatibility	Reduce SKUS

SIZE	PART NUMBER	CORE
24" x 100'	382400001509	2"
36" x 100'	382400002409	2"
42" x 100'	382400002909	2"
50" x 100'	382400003709	2"
60" x 100'	382400004509	2"

**PRINTER**

Hewlett Packard DJ 5000 / 5500  
Encad

**INK**

Dye / UV

**FINISHING RECOMENDATIONS**

Protect prints imaged with dye inks under glass or laminate to increase gas-fastness.  
Use low melt or pressure sensitive laminates to extend the life of the print and increase its durability.  
For best results use thinner and flexible laminates.  
Allow 24 hours for ink to cure before protecting image.

**STORAGE CONDITIONS**

Temperature 59o-86oF. (15°-30°C).  
Repack opened rolls when not in use.  
One year shelf life at conditions noted above.  
Allow material to stabilize to room conditions for 24 hours before use.