

38670

Instant Dry / Microporous White Film with Gray Back - GLOSS 7 mil

PRODUCT DESCRIPTION

38670 is a white polyester film with a brilliant white glossy finish for outstanding "color pop" and a grayback for 100% lightblock. The durable construction is engineered to withstand repeated rolling in portable display units without tearing or edge fraying. The light-blocking layer eliminates image washout caused by light diffusion.

SPECIFICATIONS

Caliper	7 mil
Gloss (60°)	50
Opacity	100%

*All values listed are target values

FEATURE	ADVANTAGE
7 mil Polyester No-Tear Base	Very Durable
Co-Extruded	Very Durable - Not a laminated base
Outstanding Lamination Bond	Indestructable graphics
High Gloss Photo Finish	Outstanding Print Quality
Lay Flat	Reduces curl and cupping
Grayback on backside	100% opacity, blocks showthrough
Universal Compatibility	Reduce SKUS
Instant Dry / Water Resistant	Faster Production

SIZE	PART NUMBER	CORE
24" x 100'	386700001509	2"
36" x 100'	386700002409	2"
42" x 100'	386700002909	2"
50" x 100'	386700003709	2"
60" x 100'	386700004509	2"

PRINTER

Hewlett Packard DJ Z 2100, 3100, 6100
Hewlett Packard DJ 5000 / 5500 /
Epson Pro 4000, 7600, 9600, 10600
Epson Stylus Pro 4800, 4880, 7800, 7880, 9800, 9880, 11880
Canon iPF 5000, 5100, 6100, 8000, 8100, 9000, 9100

INK

Vivera Pigment
Dye / UV
Ultra Chrome
K3
Lucia Pigment

FINISHING RECOMENDATIONS

Protect prints imaged with dye inks under glass or laminate to increase gas-fastness.
Use low melt or pressure sensitive laminates to extend the life of the print and increase its durability.
For best results use thinner and flexible laminates.
Allow 24 hours for ink to cure before protecting image.

STORAGE CONDITIONS

Temperature 59o-86oF. (15°-30°C).
Repack opened rolls when not in use.
One year shelf life at conditions noted above.
Allow material to stabilize to room conditions for 24 hours before use.