

56650

Fast Dry Backlit Film - Matte

6.5 mil

PRODUCT DESCRIPTION

56650 is a 6.5 mil, fast dry, matte surface front-print polyester backlit film backlit film designed to deliver amazing colors and density with pigment based thermal and piezo printers and can be displayed with either daylight or backlight.

SPECIFICATIONS

Caliper	6.5 mil
Gloss	Matte
Opacity	82%

*All values listed are target values

FEATURE	ADVANTAGE
Matte Finish (Front Surface) / Front Print	Reduced glare
Premium Polyester Base	Dimensionally Stable / Tear Resistant
Brilliant, Vivid Colors	Simulate Duratrans
Fast Drying	Faster Production
Excellent Color Gamut	Color Matching
High Ink Load	Rich Colors / Dark Blacks
Universal Compatibility	One Sku For All Printers

SIZE	PART NUMBER	CORE
24" x 100'	566500001509	2"
36" x 100'	566500002409	2"
42" x 100'	566500002909	2"
44" x 100'	566500003109	2"
50" x 100'	566500003709	2"
54" x 100'	566500004109	2"
60" x 100'	566500004509	2"

PRINTER

Hewlett Packard DJ Z 2100, 3100, 6100
 Hewlett Packard DJ 5000 / 5500 /
 Epson Pro 4000, 7600, 9600, 10600
 Epson Stylus Pro 4800, 4880, 7800, 7880, 9800, 9880, 11880
 Canon iPF 5000, 5100, 6100, 8000, 8100, 9000, 9100

INK

Vivera Pigment
 Dye / UV
 Ultra Chrome
 K3
 Lucia Pigment

FINISHING RECOMENDATIONS

Protect prints imaged with dye inks under glass or laminate to increase gas-fastness.
 Use low melt or pressure sensitive laminates to extend the life of the print and increase its durability.
 For best results use thinner and flexible laminates.
 Allow 24 hours for ink to cure before protecting image.

STORAGE CONDITIONS

Temperature 59o-86oF. (15°-30°C).
 Repack opened rolls when not in use.
 One year shelf life at conditions noted above.
 Allow material to stabilize to room conditions for 24 hours before use.