



73333

FSC Certified Presentation Paper - 140 g/m² 7 mil

PRODUCT DESCRIPTION

73333 - FSC Certified – 140 g/m² coated matte inkjet paper is a bright white matte inkjet paper . Designed for maximum color gamut and superior post process lamination 73333 has an fast dry, water resistant, matte coating with 98% opacity, which minimizes show through when posting on irregular or non-white surfaces.

SPECIFICATIONS

Caliper	7 mil
Weight	140g/m ²
Gloss (60°)	matte
Opacity	>98%

*All values listed are target values

FEATURE	ADVANTAGE
FSC Certified	"Green" Choice for Matte Paper
Bright White	
Excellent Line Definition	Good Line Acuity
Fast Dry	Faster Production
High Color Density	Rich Colors / Dense Blacks
Universal Compatibility	Reduce SKUs - Works On All Printers
Good K Density	Excellent for Display and Technical Graphics

SIZE	PART NUMBER	CORE
24" x 100'	7333300015H9	2"
36" x 100'	7333300024H9	2"
42" x 100'	7333300029H9	2"
50" x 100'	7333300037H9	2"
60" x 100'	7333300045H9	2"

PRINTER

Hewlett Packard DJ Z 2100, 3100, 6100
Hewlett Packard DJ 5000 / 5500 /
Epson Pro 4000, 7600, 9600, 10600
Epson Stylus Pro 4800, 4880, 7800, 7880, 9800, 9880, 11880
Canon iPF 5000, 5100, 6100, 8000, 8100, 9000, 9100

INK

Vivera Pigment
Dye / UV
Ultra Chrome
K3
Lucia Pigment

FINISHING RECOMENDATIONS

Protect prints imaged with dye inks under glass or laminate to increase gas-fastness.
Use low melt or pressure sensitive laminates to extend the life of the print and increase its durability.
For best results use thinner and flexible laminates.
Allow 24 hours for ink to cure before protecting image.

STORAGE CONDITIONS

Temperature 59o-86oF. (15°-30°C).
Repack opened rolls when not in use.
One year shelf life at conditions noted above.
Allow material to stabilize to room conditions for 24 hours before use.