

73988

Outdoor Adhesive Backed Vinyl - Matte

6 mil / 5 mil

PRODUCT DESCRIPTION

73988 is a premium outdoor vinyl with excellent outdoor durability and fade resistance with aqueous inkjet printers. **73988**, starts with a calendered vinyl base and lay flat paper release liner. The matte, outdoor durable coating produces vivid color graphics, ideal for the most extreme applications.

SPECIFICATIONS

Caliper	6 mil /11 mil with liner
Gloss (60°)	matte
Opacity	>98%

*All values listed are target values

FEATURE	ADVANTAGE
Flexible PVC Base	Conforms to uneven surfaces
Waterfast Coating	Outdoor Durable
Permanent / Solvent Adhesive	Long Lasting Outdoors
Universal Compatibility	Reduce SKUs
Extreme Outdoor Coating	Long Lasting Outdoors
Excellent Lamination Properties	Create durable graphics
Lay Flat Release Liner	Easy to apply to mounting surface
Outdoor Durable - 1 year without lamination	Arternative to Solvent Inkjet

SIZE	PART NUMBER	CORE
24" x 65'	7398800015H6	2"
36" x 65'	7398800024H6	2"
42" x 65'	7398800029H6	2"
50" x 65'	7398800037H6	2"
60" x 65'	7398800045H6	2"

PRINTER

Hewlett Packard DJ Z 2100, 3100, 6100
Hewlett Packard DJ 5000 / 5500 /
Epson Pro 4000, 7600, 9600, 10600
Epson Stylus Pro 4800, 4880, 7800, 7880, 9800, 9880, 11880
Canon iPF 5000, 5100, 6100, 8000, 8100, 9000, 9100

INK

Vivera Pigment
Dye / UV
Ultra Chrome
K3
Lucia Pigment

FINISHING RECOMENDATIONS

Protect prints imaged with dye inks under glass or laminate to increase gas-fastness.
Use low melt or pressure sensitive laminates to extend the life of the print and increase its durability.
For best results use thinner and flexible laminates.
Allow 24 hours for ink to cure before protecting image.

STORAGE CONDITIONS

Temperature 59o-86oF. (15°-30°C).
Repack opened rolls when not in use.
One year shelf life at conditions noted above.
Allow material to stabilize to room conditions for 24 hours before use.



Arkwright Advanced Coating, Inc.
538 Main Street, Fiskeville, RI 02823,
p. 401.821.1000, f. 401.826.3926
www.arkwright.com

Arkwright is a registered trademark of Arkwright Advanced Coating, Inc © 2009