

73999

Instant Dry / Microporous Photo Paper GLOSS 8 mil

PRODUCT DESCRIPTION

73999 is the ultimate GLOSS photopaper ideal for any photographic or display graphics application. The bright white microporous topcoat means your prints will be instantly dry and water resistant while the 8 mil base allows you to save money and still provide premium photographic quality output. Wide color gamut and accurate skin tones are standard with all Arkwright photopapers, yet 73999 also boasts superior shadow detail and extremely low dot gain. 73999 is optimized for today's wide gamut pigment ink photo quality printers such as Canon, Epson and HP.

SPECIFICATIONS

Caliper	8 mil
Basis Weight	200 g/m ²
Gloss (60°)	52
Opacity	>92%

*All values listed are target values

FEATURE	ADVANTAGE
High Quality Resin Coated Base	Premium "Hand"
Neutral White	Nuetral Color
Exceptional Color Gamut	Color Matching
Instant Dry	Increased Production
Water Resistant	Print not ruined from a little water
Universal Compatibility	Reduce skus
Excellent Lamination Properties	Faster Production

SIZE	PART NUMBER	CORE
24" x 100'	7399900015H9	2"
36" x 100'	7399900024H9	2"
42" x 100'	7399900029H9	2"
50" x 100'	7399900037H9	2"
60" x 100'	7399900045H9	2"

PRINTER

Hewlett Packard DJ Z 2100, 3100, 6100
Hewlett Packard DJ 5000 / 5500 /
Epson Pro 4000, 7600, 9600, 10600
Epson Stylus Pro 4800, 4880, 7800, 7880, 9800, 9880, 11880
Canon iPF 5000, 5100, 6100, 8000, 8100, 9000, 9100

INK

Vivera Pigment
Dye / UV
Ultra Chrome
K3
Lucia Pigment

FINISHING RECOMENDATIONS

Protect prints imaged with dye inks under glass or laminate to increase gas-fastness.
Use low melt or pressure sensitive laminates to extend the life of the print and increase its durability.
For best results use thinner and flexible laminates.
Allow 24 hours for ink to cure before protecting image.

STORAGE CONDITIONS

Temperature 59o-86oF. (15°-30°C).
Repack opened rolls when not in use.
One year shelf life at conditions noted above.
Allow material to stabilize to room conditions for 24 hours before use.